

Listing of the Claims:

1. (Currently Amended) An apparatus for cleaning a window positioned between a passenger compartment of a truck and a cab enclosing a bed of the truck comprising:

a single, unitary, generally planar elongate body having a first enlarged end, an elongate middle portion, and a second enlarged end opposite from the first end; and

at least one hand-grip portion integrally formed as one piece with the body, the hand-grip portion located along ~~at least one outer peripheral edge of a~~ peripheral surface defining an outer longitudinal end of at least one enlarged end of the body; and

a plurality of ribs integrally formed on the body for stiffening the body.

2. (Original) The apparatus of claim 1 further comprising:

a replaceable soft material cleaning cover engagable on the first enlarged end.

3. (Original) The apparatus of claim 2, wherein the first enlarged end further comprises:

means for gripping the replaceable soft material cleaning cover.

4. (Currently Amended) The apparatus of claim 3, wherein the gripping means further comprises a plurality of hooks integrally formed on the body adjacent to the transition between a longitudinally extending side and an inner end of the enlarged end portion for engagement with the cover.

5. (Original) The apparatus of claim 2, wherein the cover further comprises one of a cleaning mitt and a sponge.

6. (Original) The apparatus of claim 1 further comprising:
a squeegee formed integrally on the second enlarged end.

7. (Cancelled)

8. (Currently Amended) The apparatus of claim 7 1, wherein the ribs are located along outer peripheral edges of the body and extending transversely along the body between peripheral edges.

9. (Currently Amended) The apparatus of claim 7 1, wherein the ribs extend transversely across a surface of the middle portion from a notch formed along one side to another notch from along an opposite side in a zig-zag pattern, ~~the a~~ plurality of notches formed in ~~opposite sides~~ opposing longitudinal sides of the middle portion spaced longitudinally from one another along the longitudinal length of the middle portion of the body and extending inwardly toward one another.

10. (Original) The apparatus of claim 1, wherein the body is formed of a thermoplastic injection molded material.

11. (Currently Amended) An apparatus for cleaning a window positioned between a passenger compartment of a truck and a cab enclosing a bed of the truck comprising:

a single, unitary, generally planar, elongate body having a first enlarged end, an elongate middle portion, and a second enlarged end opposite from the first end; and

at least two hand-grip portions integrally formed on the body, one hand-grip portion formed as one piece with the body along ~~an outer peripheral edge~~ a peripheral surface defining an outer longitudinal end of each enlarged end of the body.

12. (Original) The apparatus of claim 11 further comprising:
a replaceable soft material cleaning cover engagable with the first
enlarged end.

13. (Original) The apparatus of claim 12, wherein the enlarged end
further comprises:
means for gripping the cleaning cover.

14. (Currently Amended) The apparatus of claim 13, wherein the
gripping means further comprise a plurality of hooks integrally formed on the first
enlarged end adjacent to the transition between a longitudinally extending side and an
inner end of the enlarged end portion for engagement with the cleaning cover.

15. (Original) The apparatus of claim 12, wherein the covering further
comprises one of a cleaning mitt and a sponge.

16. (Original) The apparatus of claim 11 further comprising:
a plurality of ribs integrally formed on the body for stiffening the body.

17. (Original) The apparatus of claim 16, wherein the ribs are located
along outer peripheral edges of the body and extending transversely along the body
between peripheral edges.

18. (Currently Amended) The apparatus of claim ~~14~~ 16, wherein the
ribs extend transversely across a surface of the middle portion from a notch formed
along one side to another notch from along an opposite side in a zig-zag pattern, ~~the a~~
plurality of notches formed in opposite sides opposing longitudinal sides of the
middle portion spaced longitudinally from one another along the longitudinal length
of the middle portion of the body and extending inwardly toward one another.

19. (Original) The apparatus of claim 11 further comprising:
a squeegee portion integrally formed on the second enlarged end.

20. (Original) The apparatus of claim 11, wherein the body is formed of a thermoplastic injection molded material.

21. (Currently Amended) An apparatus for cleaning a window positioned between a passenger compartment of a truck and a cab enclosing a bed of the truck comprising:

a single, unitary, generally planar elongate body having a first enlarged end, an elongate middle portion, and a second enlarged end opposite from the first end, wherein the body is formed of a thermoplastic injection molded material;

a plurality of integral ribs formed on the body for stiffening the body, wherein the ribs extend transversely across a surface of the middle portion from a notch formed along one side to another notch from along an opposite side in a zig-zag pattern, the notches formed in opposite sides of the middle portion spaced longitudinally from one another along the longitudinal length of the middle portion of the body and extending inwardly toward one another;

a squeegee formed integrally on the second enlarged end;

at least one hand-grip portion integrally formed as one piece with the body, the hand-grip portion located along ~~at least one outer peripheral edge~~ a peripheral surface defining an outer longitudinal end of at least one enlarged end of the body;

a replaceable soft material cleaning cover engagable on the first enlarged end, wherein the cover includes one of a cleaning mitt and a sponge; and

means for gripping the replaceable soft material cleaning cover, wherein the gripping means includes a plurality of hooks integrally formed on the body adjacent to the transition between a longitudinally extending side and an inner end of the enlarged end portion for engagement with the cover.

Date July 13, 2005

Reply to Office Action dated July 7, 2005

22. (Currently Amended) The apparatus of claim ~~20~~ 21, wherein the at least one hand-grip portion further comprises:

a first hand-grip portion located along an outer peripheral edge of the first enlarged end; and

a second hand-grip portion located along an outer peripheral of the second enlarged end.